

SYSTEM AND METHOD FOR MAINTAINING STATE INFORMATION ON A CLIENT

Technical Field

The present invention relates to a system and method for maintaining state information on a client. More particularly, the present invention relates to transmitting from a server an unmodifiable cookie for storage on a client machine in response to a predefined request to the server.

Background of the Invention

The World Wide Web of the Internet is the most successful distributed application in the history of computing. The architecture of the Web follows a conventional client-server model. The terms "client" and "server" are used to refer to a computer's general role as a requester of data (the client) or provider of data (the server). Under the Web environment, Web browsers reside in clients and Web documents reside in servers. Web clients and Web servers communicate using a protocol called "HyperText Transfer Protocol" (HTTP). A browser opens a connection to a server and initiates a request for a document. The server delivers the requested document, typically in the form of a text document coded in a standard Hypertext Markup Language (HTML) format, and when the connection is closed in the above interaction, the server serves a passive role, i.e., it accepts commands from the client and cannot request the client to perform any action.

In the Internet paradigm, a network path to a server is identified by a so-called Uniform Resource Locator (URL) having a special syntax for defining a network connection. Use of an HTML-compatible browser (e.g., Netscape Navigator) at a client machine involves specification of a link via the URL. In response, the

09740537 121800

SYSTEM AND METHOD FOR MAINTAINING STATE INFORMATION ON A CLIENT**Technical Field**

The present invention relates to a system for and a method of maintaining state information on a client. More particularly, the present invention relates to transmitting from a server an unmodifiable cookie for storage on a client machine in response to a predefined request to the server.

Background of the Invention

The World Wide Web of the Internet is the most successful distributed application in the history of computing. The architecture of the Web follows a conventional client-server model. The terms "client" and "server" are used to refer to a computer's general role as a requester of data (the client) or provider of data (the server). Under the Web environment, Web browsers reside in clients and Web documents reside in servers. Web clients and Web servers communicate using a protocol called "HyperText Transfer Protocol" (HTTP). A browser opens a connection to a server and initiates a request for a document. The server delivers the requested document, typically in the form of a text document coded in a standard Hypertext Markup Language (HTML) format, and generally when the connection is closed in the above

09740527-121300

interaction, the server serves a passive role, i.e., it accepts commands from the client and cannot request the client to perform any action.

In the Internet paradigm, a network path to a server is identified by a so-called Uniform Resource Locator (URL) having a special syntax for defining a network connection. Use of an HTML-compatible browser (e.g., Netscape Navigator) at a client machine involves specification of a link via the URL. In response, the client makes a request to the server identified in the link and receives in return a document formatted according to HTML.

Information in web pages accessed over the Internet commonly is downloaded into the client computer system. In addition to downloading the web page, the web server also may transmit a "cookie" to the browser and receive previously transmitted cookies stored in the permanent memory of the browser.

With reference to Internet transactions, a cookie is a packet of information sent by an HTTP server to a World Wide Web browser and then sent back by the browser each time the browser accesses that server. Cookies can contain any arbitrary information the server chooses, subject to the standards acceptable to a browser, and are used to maintain state between otherwise stateless HTTP transactions. Typically cookies are used to authenticate

008777 22504260

or identify a registered user of a web site without requiring them to sign in each time they access that site. Other uses for cookies include, e.g. maintaining a "shopping basket" of goods a user selects to purchase during a session at a site, site personalization and, tracking a particular user's access to a site.

Figure 1 is a flow diagram of a process 100 illustrating how a typical browser operates. The user either selects a hyperlink in a Web browser or specifies a link in a browser, step 102. The client system examines its cookie list for matching cookies that need to be sent to the particular Web server, step 104. Specifically, before the client sends an HTTP request to a Web server, the client compares the URL of the requested Web document against all of the stored cookies. If any of the cookies in the cookie list matches the requested URL then information containing the name/value pairs of the matching cookies is sent along with the HTTP request, step 106. If there are no cookies that match the requested URL then the browser sends the request to the server, step 108. The browser receives the response from the server, step 110. The browser then looks for a cookie in the response from the server, step 112. Any cookies present in the response are stored on the hard drive of client machine, step 114 and the requested page is displayed, step 116. In the event a cookie is not

09740527 121800

present in the response from the server, the requested page is still displayed, step 116. This process is repeated with each hyperlink selected by the user, step 118. When no hyperlink is selected, the process stops, step 120.

Web merchants commonly use cookies to track subscriptions they provide for Web content such as newsletters, magazines, etc. To entice potential permanent subscribers, the Web merchant often provides a free trial subscription to a user. The trial subscription is tracked using a cookie and once the free period expires, the merchant notifies the user in hopes that the user will purchase a subscription. This marketing model is not without its problems for example, the user has the ability to change his identity and register a subsequent time for the same free subscription. This can be done by removing and/or modifying the cookie resident on his computer. The merchant then loses a potential subscriber. Therefore, an unmodifiable cookie that resides on the client machine would help to alleviate this problem.

09740527.12.1300

Summary of the Invention

The present invention provides a method of maintaining state information on a client. A client requests a file located on a server. In response to the request, the file is transmitted from the http server to the http client. An unmodifiable cookie which specifies state information from the http server is also transmitted to the http client. The client then stores the unmodifiable cookie.

In carrying ou the above described method, a computer readable medium on a client containing executable program instructions is utilized. The program requests a file on a http server; receives the file from the http server; receives an unmodifiable cookie which specifies state information from the http server; and causes the unmodifiable cookie to be stored on the http client.

In addition, a computer readable medium on a server is provided. The computer readable medium contains executable program instructions for receiving a request for a file on the http server from a client, transmitting the file from the http server to the http client, and transmitting an unmodifiable cookie which specifies state information from the http server to the http client.

In addition, a computer system is provided in accordance with the present invention. The computer system comprises a processor; a memory coupled to the

09740527 121300

processor; a computer readable medium coupled to the processor that contains instructions to carry out the methods described above for the server and the client.

09740527 121800

[illegible]

Figure 5 is a flow diagram of a server process in accordance with the present invention.

Detailed Description of the Preferred Embodiment

The present invention is directed to a method of and a system for a server to ensure identification of a web client by installing a user unmodifiable cookie file in the web client's browser program.

In the examples discussed below, the server uses a hypertext transfer protocol ("HTTP") to communicate over a network with clients. The clients also communicate with the server using the HTTP. It should be noted that cookies in accordance with the present invention may be transferred via other communication protocols in addition to HTTP. Examples of other communication protocols include but are not limited to, file transfer protocol, gopher, and wireless application protocol. The present invention is applicable to any type of communication protocol where information packets are transferred between server and client.

The server typically includes a server processor, a memory and a computer readable medium, such as a magnetic ("hard disk") or optical mass storage device. The computer readable medium of the server contains computer program instructions for transmitting the file from the server system to the client system and for transmitting the cookie to the client system. The client typically includes a client processor, a memory and a computer readable medium, such as a magnetic or optical mass

09740527 121800

storage device. The computer readable medium of the client contains computer program instructions for receiving the cookie, which specifies the state information, from the server and for storing the cookie at the client.

An example of how a cookie is generated and transferred will now be discussed. It will be appreciated that alternative formats may be used in accordance with the principles of the present invention. As stated above, the extension to the HTTP protocol adds a piece of state information to the HTTP header as part of a response from a Web server. Typically, the state information is generated by a common gateway interface ("CGI") script. The state information is stored by the receiving client system in the form of a "cookie file" for later use. An example of the syntax of the new data, is:

```
Set-Cookie: NAME=VALUE; expires=DATE;
path=PATH;
domain=DOMAIN__NAME; secure
```

The capitalized terms can be set by the server system. The first attribute is "NAME=VALUE". This attribute serves to identify a cookie. The "NAME" attribute is a name for the cookie. The "VALUE" is a value assigned to the previously defined name. The "VALUE" can be a string of characters.

09740527 121800

094092-130

The "path" attribute is used to specify a subset of file system directories in a domain for which the cookie is valid. If a cookie has already passed "domain" matching, then the path name of the URL for a requested

document is compared with the "path" attribute. If there is a match, the cookie is considered valid and is sent along with the HTTP request. All the characters of the defined path must match. However there may be additional characters on the path name. Thus, further defined subdirectories will match a path to the parent directory. If no path is specified when a cookie is created, then the default path will be the same path as the document that was sent with the header which contains the cookie.

The last element of the cookie definition is the optional label of "secure." If a cookie is marked "secure," then the cookie will only be retransmitted if there is a secure communication channel to the server system. In a preferred embodiment of the present invention, this means that the cookie will only be sent to HTTPS servers. (HTTP over Secure Socket Layer) If the "secure" attribute is not specified, a cookie is considered safe to be sent over unsecured channels.

When a client system selects a hyperlink for a particular Web server, the client system first examines the cookie files on the client hard drive for matching cookies to be sent to the particular Web server. As noted above with reference to Fig. 1, before the client sends an HTTP request to a Web server, the client compares the URL of the requested Web document against all of the stored cookies. If any of the cookies stored on the hard

09740527 121300

drive match the requested URL then information containing the name/value pairs of the matching cookies will be sent along with the HTTP request. In accordance with the present invention the server sends unmodifiable cookies with the response that are stored on the client machine.

Unmodifiable cookies may be created by altering an existing cookie such that it is unmodifiable by a user. One example may include encrypting the cookie file where the encryption code is known only to the browser program. For security reasons, the encryption code would not be revealed to the user. In a preferred embodiment an unmodifiable cookie is encrypted using a symmetric encryption key. An example of suitable symmetric encryption key includes but is not necessarily limited to a Data Encryption Standard (DES) key with a 56 bit key length. The key length of symmetric encryption keys often plays a major role in preventing brute force attack on the key.

Data integrity of the unmodifiable cookie file may be ensured by applying a complex hash function to the file and storing the hash value in an encrypted form. If an unmodifiable cookie file is edited by a user (even though the user has not broken the encryption code) when the browser compares the hash functions the hash value of the modified file will not match the hash value of the encrypted file. There are many other techniques involving

09740527 131300

As with the current systems, the browser may provide the user with a choice to accept or reject "unmodifiable" cookies on their hard drive in addition to being able to accept or reject modifiable cookies. Thus the client is able to maintain control over which cookies are accepted and which are not. Alternatively, when the client desires the removal of an unmodifiable cookie, the server that issued the cookie is capable of removing or disabling the cookie on the client's hard drive.

Figure 1A shows, in more detail, an example of a client-server system connected through the Internet 121. In this example, a remote server system 122 is connected through the Internet 121 to client system 124. The client system 124 includes conventional components such as a processor 126, memory 128 (e.g. RAM), a bus 130 which couples the processor 126 and memory 128, a mass storage device 132 (e.g. a magnetic hard disk or an optical storage disk) coupled to the processor and memory through an I/O controller 134 and a network interface 136, such as a conventional modem. The server system 122 also includes conventional components such as a processor 138,

memory 140 (e.g. RAM), a bus 142 which couples the processor 138 and memory 140, a mass storage device 144 (e.g. a magnetic or optical disk) coupled to the processor 138 and memory 140 through an I/O controller 146 and a network interface 148, such as a conventional modem. It will be appreciated from the description below that the present invention may be implemented in software which is stored as executable instructions on a computer readable medium on the client and server systems, such as mass storage devices 132 and 144 respectively, or in memories 128 and 140 respectively.

Figure 2 is a schematic illustration of a client system according to the present invention. The CPU or hard drive 200 communicates over a network through a browser 202. The cookies transmitted from various servers visited by the user are stored in a public cookie file 204 and if they are labeled "unmodifiable" then a copy is stored in a separate "private" cookie file 206. As discussed above, the private cookie file contains unmodifiable cookie information.

Figure 3 is a flow diagram of process 300 in accordance with a preferred embodiment of the present invention. A user selects a hyperlink using a browser, step 302. The browser checks the cookie files resident on the hard drive for a cookie that matches the requested domain of the hyperlink, step 304. If a matching cookie

09740537 "121800

is not present, then the browser sends the HTTP request on to the server, step 306. If a matching cookie is present on the client machine, then the browser will compare the cookie in the public cookie file with the cookies in the protected cookie file, step 308, which is discussed in more detail below with reference to Figure 4. The browser then sends the matching cookie with the HTTP request to the server, step 310. Regardless of whether the browser sent a cookie with the HTTP request, steps 306 and 310, the browser will receive a response from the server, step 312. The browser examines the response sent in step 312 for a cookie, step 314. If a cookie is present in the response from the server, then the browser checks to see if the cookie is unmodifiable, step 316. If an unmodifiable cookie is present, it is saved in a private cookie file, step 318 and a copy of the unmodifiable cookie is saved in the public cookie file, step 320. If the cookie is not unmodifiable, then the cookie is saved in the public cookie file on the hard drive, step 320. Once the cookie is stored on the hard drive, the requested page is displayed, step 322. Likewise, if in step 314 there is no matching cookie found in the response from the server, then the requested page is simply displayed, step 322. If the user selects an additional hyperlink, step 324, the process repeats itself starting at step 304. If no hyperlink is

009740527 131800

[illegible]

Figure 5 is a flow diagram of a server process 500 in accordance with the present invention. The server receives a request from the client, step 502. The server sends a response to the client with an unmodifiable cookie, step 504. The server checks the client response for acceptance or rejection of the unmodifiable cookies,

step 506. If the unmodifiable cookie is rejected, then the server sends a message to the client stating that it will not allow access to the requested material unless the client accepts unmodifiable cookies, step 508. If the client machine is configured to accept unmodifiable cookies, then the server allows the client to view the requested page, step 510.

While the invention has been shown and described with reference to particular embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and detail may be made therein without departing from the spirit and scope of the invention.

09740527 121800